

STRUCTURAL RACK SYSTEMS



UNARCO MATERIAL HANDLING, INC.

Corporate Headquarters

701 16th Avenue East
Springfield, Tennessee 37172

phone: 1-800-862-7261
fax: (248) 347-2380

www.UNARCORACK.com

Manufacturing Facilities

501 East Purnell Street
Lewisville, Texas 75057
phone: 1-800-283-4622
fax: (972) 436-7901

407 East Washington
Pandora, Ohio 45877
phone: 1-800-448-0784
fax: (419) 384-7239

701 16th Avenue East
Springfield, Tennessee 37172
phone: 1-800-862-7261
fax: (615) 382-2777



UNARCO MATERIAL HANDLING, INC.



UNARCO was the first pallet rack manufacturer in the industry. With fifty years in production, engineering and design, no one offers more experience in how to increase efficiency in warehouses and distribution centers.

Flexibility that you will not find in other large pallet rack manufacturers stems from the ability to produce an entire line of warehouse storage solutions including carton flow, pallet flow, push back, drive-in/drive-thru and cantilever. But more importantly, UNARCO has structured its customer service and manufacturing facilities to LISTEN to customers' needs and respond with custom designs and smarter solutions.



WWW.UNARCORACK.COM

HIGH-STRENGTH STRUCTURAL STEEL

UNARCO Structural Racks are designed to prevent damage from forklift abuse. The posts are constructed from structural steel and are much thicker than roll-formed posts, particularly at the corners which are the primary impact points.



Automated Storage and Retrieval Systems

Structural upright with structural beam


STRUCTURAL BOLTED

Heavy-duty 3" or 4" structural steel C-Channels have pre-punched bolt holes on 4" centers. Structural steel beams include beam connectors that are punched on 2" centers for 2" vertical beam adjustability.

Structural upright with roll-formed beam

RIGIDITY EFFICIENT ECONOMICAL

Unarco Engineering uses the high strength and durability of structural steel for large projects with heavy loads or highly engineered pick modules.



STRUCTURAL INTERCHANGEABLE

Heavy-duty 3" structural steel C-Channels have pre-punched tear drop openings on 2" centers. This design combines the ruggedness of structural steel uprights and the efficiency of roll-formed step beams.

Structural upright with structural beam

Structural upright with roll-formed beam

Structural posts with interchangeable punching

- Strength
- Ductility
- Easily Repaired
- Abuse Resistant
- Heavy-Duty Structural Bracing

ENGINEERING

INSTALLATION

PROJECT MANAGEMENT





STRUCTURAL UPRIGHTS

UPRIGHT FRAME SELECTION


STRUCTURAL CHANNEL FRAME TABLES BOLTED

COLUMN SIZE	C3 x 3.5#	C3 x 4.1#	C4 x 4.5#	C4 x 5.4#
Shelf Space	40" Pan.	40" Pan.	40" Pan.	40" Pan.
36"	27,515	29,821	44,172	47,134
42"	27,515	29,821	44,172	47,134
48"	27,515	29,821	44,172	47,134
54"	27,515	29,821	44,172	47,134
60"	27,515	29,821	44,172	47,134
66"	27,515	29,821	44,172	47,134
72"	27,320	28,037	44,172	47,134
78"	23,940	24,400	44,172	47,134
84"	20,724	21,033	44,126	46,257
90"	18,053	18,322	40,610	42,229
96"	15,867	16,103	37,162	38,328


* Indicated in pounds.

STRUCTURAL CHANNEL FRAME TABLES TEAR DROP


COLUMN SIZE	C3 x 3.5#
Shelf Space	40" Pan.
36"	26,848
42"	26,848
48"	26,848
54"	26,848
60"	26,848
66"	26,848
72"	26,657
78"	23,360
84"	20,222
90"	17,616
96"	15,483



STRUCTURAL INTERCHANGEABLE



STRUCTURAL BOLTED



All values in the above tables assume that each column carries half of the frame load. The table values are expressed in pounds per frame. These values are based on gravity loading only that is purely axial. Any condition where the axial load is accompanied by moment, the axial load capacity will be less. This will occur for non-symmetrical loading conditions. The capacities also assume that the baseplates and the bracing are of adequate strength and that all other parts of the rack have been properly designed. All values are for undamaged racks that are installed plumb. It is the rack user's responsibility to properly maintain the racks to ensure that the carrying capacity of the racks is not reduced by damage and that any changes to the rack configuration do not cause an unsafe condition.

Frame capacities are based on the unsupported length, which is the measurement of the distance between the floor and the top of the first beam or the maximum spacing between beams, whichever governs.

Refer to www.unarcorack.com for latest updates to installation instructions, user manuals and safety notices.

Capacities do not take seismic, wind or other lateral forces into consideration.


Upright frames have to be anchored with at least one anchor bolt in each post and require a minimum concrete floor strength of 3,000 PSI for the maximum loads.

CONTACT THE UNARCO SPRINGFIELD OFFICE FOR ANY OF THE FOLLOWING CONDITIONS:

- Any application where the frame load exceeds 31,000 lbs. These frames may need larger base plates or heavier bracing.
- Any application that requires seismic design where the design ground acceleration S_s exceeds 25%g in IBC areas.
- Configurations that require a frame deeper than 60 inches or higher than 40 feet.
- Applications that involve support platforms or catwalks or any application other than normal pallet rack.
- Any single row where the height-to-depth ratio exceeds 6 to 1. These must be checked for anchorage against overturning.
- Any condition which creates uncertainty as to the proper use of these tables.

Column protection is recommended for uprights subjected to potential column abuse from lift trucks.


STRUCTURAL BEAMS



BEAM CAPACITY CHART (indicated in pounds)

COLUMN SIZE	C3 x 3.5#	C3 x 4.1#	C4 x 4.5#	C4 x 5.4#	C5 x 6.7#	C6 x 8.2#
	W/O Tie	W/ Tie	W/O Tie	W/ Tie	W/O Tie	W/ Tie
48"	12,593	12,858	13,521	13,632	16,000	16,000
60"	9,602	10,470	10,364	11,100	15,246	16,000
72"	7,577	8,680	8,231	9,057	11,801	14,074
84"	6,106	6,502	6,683	6,777	9,046	11,900
90"	5,402	5,716	5,954	5,954	7,865	11,028
96"	4,777	5,068	5,276	5,276	6,904	10,263
102"	4,258	4,527	4,709	4,709	6,112	9,486
108"	3,821	4,070	4,231	4,231	5,451	8,493
114"		3,680	3,824		7,650	8,015
120"		3,345	3,473		6,928	7,255
126"		3,054	3,169		6,304	6,598
132"		2,800	2,903		5,760	6,026
138"		2,577	2,669		5,285	5,525
144"		2,379	2,463		4,865	5,084
150"		2,203	2,279		4,494	4,692
156"		2,046	2,114		4,163	4,344


- All capacities are expressed in pounds per pair of beams. Only gravity loading and the RMI required impact have been considered.
- All values are based on a uniformly distributed load (i.e. each beam carries 50% of the load) and assume proper installation and no beam damage.
- The deflection limit for all beams is the length divided by 180.
- Beams that are longer than 108" require lateral ties.
- Values in the table are for the beam bending only.
- Please consult Springfield Engineering for any shelf load over 10,000 lbs.
- Capacities include 12.5% impact for two pallets side by side. For a three-pallet-wide shelf, the values should be multiplied by 0.95.
- For one pallet per shelf, the values should be multiplied by 0.90.
- Capacity chart is based on current RMI specifications.



UNARCO rack designs conform to the latest Rack Manufacturers Institute (RMI) specifications and AISI Cold Formed Steel Design Manual using "Load and Resistance Factor Design" (LRFD) Method.

Refer to www.unarcorack.com for latest updates to installation instructions, user manuals and safety notices.


WWW.UNARCORACK.COM



- | | |
|----------------------------|---------------------------------|
| 1. Lateral Tie | 9. Double Column |
| 2. Structural Crossbar | 10. Anchored Column Protector |
| 3. Overlap Crossbar* | 11. Reinforced Post/Debris Cap |
| 4. Drop-In Crossbar* | 12. Straddle Protector |
| 5. Roll-Formed Beam* | 13. Bolt-On End Of Aisle Guard |
| 6. Angled Column Protector | 14. Anchored End Of Aisle Guard |
| 7. Heavy-Duty Horizontal | 15. Wall Tie |
| 8. Seismic Baseplate | 16. Row Spacer |


* Accessories for use with structural interchangeable uprights and roll-formed beams.

DURABILITY OPTIONS




FRAME OPTIONS

- Helps reduce the risk of forklift impact to uprights with special designs which set the base out of harm's way
- Improves aisle clearance



RACK ACCESSORIES



(For roll-formed beams only)


(For roll-formed beams only)



STRUCTURAL DRIVE-IN/DRIVE-THRU RACKS

UNARCO Structural Drive-In and Drive-Thru racks provide the highest density storage available. The system depth reduces the need for aisles and increases space utilization.

- *Specifically for uniform pallet loads*
- *Easy to assemble*
- *Cost effective*
- *Sturdy, bolted connections*



MAXIMUM DENSITY




Drive-In: Load and retrieve from the same side (LIFO)

Drive-Thru: Load from one aisle, retrieve from separate aisle (FIFO)

Pallets are placed on rails that run the depth of the rack



Drive-In Rail with Space Saver Arm for easier placement of pallets



Straight Rail Option




STRUCTURAL PUSH BACK RACK

Push Back systems work by putting pallet loads on a series of nesting carts. As a pallet is loaded from the front, it pushes the pallet behind it back one position. When it is time to unload (LIFO), the front pallet is removed and the rear pallets automatically come forward to the front picking position.




STURDY STRUCTURAL DESIGN



PUSH BACK



2-deep system



Carts flow automatically on four sealed wheels




Strong structural sides and rails

- *Available in 2, 3, 4, 5 and 6 deep configurations*
- *Lift truck drivers never enter the rack*
- *Nesting carts require minimal vertical space*
- *Product loads are always in picking position, thanks to gravity*
- *No special pallets are required*
- *Suitable for coolers and freezers with temperatures as low as -30° F*




RECOMMENDED DIMENSIONS AND CLEARANCES



TYPICAL BAY OPENINGS

If load overhangs pallet, the load width must be used to calculate clearances and beam length.



RACK REPAIR

Trained technicians can install bolt-on options to fix low-level damage with specially designed repair kits.

- In most cases no welding is required
- Installs easily into existing rack of any manufacturer
- Available in structural or tubular roll-formed versions

Before attempting to repair damaged rack and to insure rack capacities are adequate, please consult Springfield Engineering.

Rack repair kits should only be installed by trained personnel.

Let Unarco set up a scheduled inspection and maintenance program to help insure the safety of your warehouse.

Available in welded and bolted options



Double-Column Structural Selective Pallet Rack

SLOPED REPAIR KIT



Reduce the risk of on-going forklift damage with sloped leg kits which take the front post out of the traffic path.

STRAIGHT LEG REPAIR KIT



Connection splice (included with kit) may be welded on-site or bolted.

BOLTED OPTION

Fasten repair kit on-site with no welding

UNARCO STANDARD COLORS

High-quality powder coated finishes for durability and rust resistance



Contact a UNARCO representative for special finish requests.
Hot-dipped galvanized finish also available.